LED Canopy

Canopy Light LED 7430 Lumens 55 Watt 4000K





Electrical	
Watt	55
Voltage	100-277VAC
Power Factor	>0.9
Total Harmonic Distortion (THD)	≤20%
Max. Operating Temperature	-35°C to 40°C
Light	
Initial Lumens	7430
Lumens per Watt	135
Color Temperature	4000K
Color Rendering (CRI)	84
Agency Approvals	
DLC Premium	Yes
UL / RoHS	Yes
Product Details	
Housing Material	Cast Aluminum
Warranty	5 year limited 6 hours per day
Rated Life	50,000 hours

PRODUCT DESCRIPTION

EarthTronics Canopy LED fixture delivers excellent energy savings compared to similar linear fluorescent and HID fixtures. This 55 watt fixture produces 7430 lumens which is suitable for 8-15' mounting heights. This fixture features excellent color properties 4000K color temperature with a high 80+ CRI providing exceptional visual acuity. The durable cast aluminum alloy housing provides excellent heat dissipation providing 50,000 hour rated life. IP65 wet rated. DLC Premium listed.

PRODUCT FEATURES

- Slim design for low ceiling
- · Durable cast aluminum housing
- 4000K, 80 CRI
- DLC Premium
- · Wide pattern light distribution
- · Mounts direct to surface
- IP65 Wet location covered ceiling only
- 3/4" conduit entry on top, 1/2" on side
- 50,000 hour rated life

APPLICATIONS

- Parking Garage
- Low Bay Areas
- Security
- Exterior Canopies
- Perimeter Lighting
- Entryways

DIMENSIONS: 7-3/8" L x 7-3/8" W x 3-15/16" H

3-15/16" H

9-7/8" L x 9-7/8" W (Outer Edge)

MODEL NUMBER: CA01750040BK1

DLC PRODUCT ID: PL8T8CXM17JD

ORDER CODE: 10802

PRODUCT WEIGHT: 5 LBS

UPC: 840791108024









7-3/8" [